

**Floorstanding cistern, two-part Universal for floorstanding WC pan
82966.1**



TECHNICAL DATA

Order no.	82966.1	Mounting acc. excl.	for VARIO-outlet 70 - 220 mm LAUFEN-connection, order no. 89009.2
Certified to	EN 14055		for VARIO-outlet 220 - 305 mm only LAUFEN-connection, order no. 89902.5
matching for	Floorstanding WC pan, order no. 82380.6	Colours	see colour table
Specification	Floorstanding, consisting of two-parts Flushing mechanism Dual-Flush water condensation insulation Charge 881 – 6/3-l (5/3-l-flush, 4,5/3-l-flush)	SPECIFICATION TEXT	Floorstanding cistern, two-part Universal Laufen-PALOMBA COLLECTION, sanitary ceramic EN 14055 dimensions 400/410 x 140 x 980 mm Dual-Flush 6/3-l (5/3-l-flush, 4,5/3-l-flush) concealed water inlet top left rear, 1/2" brass matching floorstanding WC pan, order no. 82380.6 Special feature: water condensation insulation Order no. 82966.1
Water inlet	concealed top left rear, 1/2" brass		
Weight	21,0 kg		
Mounting acc. incl.	Fastening kit Angle valve for rear water inlet Water inlet hose		

TECHNICAL DRAWINGS / S 1 : 20

